# EAST Search History

| Ref # | Hits | Search Query | DBs | Default Operator | Plurals | Time Stamp |
|---|---|---|---|---|---|---|
| L1 | 322 | ("KHANNA, RAHUL" or "ZIMMER, VINCENT") | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:10 |
| L7 | 4 | "6871210" | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:17 |
| L8 | 15 | l1 and (("pre-boot" or "preboot") with authenticat$3) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:19 |
| L9 | 18 | l1 and (("pre-boot" or "preboot" or ("boot" adj "server")) with authenticat$3) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:20 |
| L10 | 32306 | "INTEL CORPORATION" | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:20 |
| L11 | 23 | l10 and (("pre-boot" or "preboot" or ("boot" adj "server")) with authenticat$3) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:33 |
| L12 | 83 | (("pre-boot" or "preboot" or ("boot" adj "server")) with authenticat$3) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:21 |
| L13 | 15 | l12 and (((operat$3 adj "system") or "OS") with ("boot" adj image$1)) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:23 |
| L14 | 0 | l13 and ((generat$3 with ("random" adj ("value" or "number"))) with "client") | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:41 |
| L15 | 637 | ((generat$3 with ("random" adj ("value" or "number"))) with "client") | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:26 |
| L16 | 153 | l15 and (((transmitt$3 or send$3) with ("random" adj ("value" or "number"))) with "server") | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:41 |

| L17 | 67 | I16 and (((encrypt$3 or encod$3) with ("random" adj ("value" or "number"))) with "server") | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:41 |
|---|---|---|---|---|---|---|
| L18 | 29 | I17 and (((decrypt$3 or decod$3) with ("random" adj ("value" or "number"))) with "client") | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:30 |
| L19 | 0 | I18 and ((compar$3 with ("random" adj ("value" or "number"))) with (("encrypt$3 or encod$3") adj "value")) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:41 |
| L20 | 0 | ((compar$3 with ("random" adj ("value" or "number"))) with (("encrypt$3 or encod$3") adj "value")) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:31 |
| L21 | 0 | I18 and ((compar$3 with ("random" adj ("value" or "number"))) with (("encrypt$3 or encod$3") with "value")) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:31 |
| L22 | 0 | ((compar$3 with ("random" adj ("value" or "number"))) with (("encrypt$3 or encod$3") with "value")) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:38 |
| L23 | 655 | 726/2.ccls. | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:32 |
| L24 | 1 | I23 and (("pre-boot" or "preboot" or ("boot" adj "server")) with authenticat$3) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:02 |
| L25 | 2700 | (("random" adj ("value" or "number")) with ((shar$3 adj "secret") or ("secret" adj "value") or "secret")) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:48 |
| L26 | 118 | I25 and ((generat$3 with ("random" adj ("value" or "number"))) with "client") | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:49 |
| L27 | 50 | I26 and (((transmitt$3 or send$3) with ("random" adj ("value" or "number"))) with "server") | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:49 |
| L28 | 26 | I27 and (((encrypt$3 or encod$3) with ("random" adj ("value" or "number"))) with "server") | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:49 |

# EAST Search History

| | | | | | | |
|---|---|---|---|---|---|---|
| L29 | 0 | I28 and ((compar$3 with ("random" adj ("value" or "number"))) with (("encrypt$3 or encod$3") adj "value")) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:50 |
| L30 | 17 | I23 and (("random" adj ("value" or "number")) with ((shar$3 adj "secret") or ("secret" adj "value") or "secret")) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:45 |
| L31 | 3 | I30 and ((generat$3 with ("random" adj ("value" or "number"))) with "client") | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:45 |
| L32 | 2 | I31 and (((transmitt$3 or send$3) with ("random" adj ("value" or "number"))) with "server") | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:45 |
| L33 | 1 | I32 and (((encrypt$3 or encod$3) with ("random" adj ("value" or "number"))) with "server") | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:48 |
| L34 | 0 | I33 and ((compar$3 with ("random" adj ("value" or "number"))) with (("encrypt$3 or encod$3") adj "value")) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:46 |
| L35 | 3608 | 713/176 | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:48 |
| L36 | 138 | I35 and (("random" adj ("value" or "number")) with ((shar$3 adj "secret") or ("secret" adj "value") or "secret")) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:53 |
| L37 | 9 | I36 and ((generat$3 with ("random" adj ("value" or "number"))) with "client") | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:54 |
| L38 | 6 | I37 and (((transmitt$3 or send$3) with ("random" adj ("value" or "number"))) with "server") | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:54 |
| L39 | 3 | I38 and (((encrypt$3 or encod$3) with ("random" adj ("value" or "number"))) with "server") | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:54 |
| L40 | 0 | I39 and ((compar$3 with ("random" adj ("value" or "number"))) with (("encrypt$3 or encod$3") adj "value")) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:55 |

| L41 | 2827 | 713/168 | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 10:53 |
|---|---|---|---|---|---|---|
| L42 | 185 | l41 and ((("random" adj ("value" or "number")) with ((shar$3 adj "secret") or ("secret" adj "value") or "secret")) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:03 |
| L43 | 22 | l42 and ((generat$3 with ("random" adj ("value" or "number"))) with "client") | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:00 |
| L44 | 4 | l43 and (((transmitt$3 or send$3) with ("random" adj ("value" or "number"))) with "server") | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:01 |
| L45 | 3 | l44 and (((encrypt$3 or encod$3) with ("random" adj ("value" or "number"))) with "server") | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:01 |
| L46 | 0 | l45 and ((compar$3 with ("random" adj ("value" or "number"))) with (("encrypt$3 or encod$3") adj "value")) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:01 |
| L47 | 998 | 713/165 | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:00 |
| L48 | 39 | l47 and ((("random" adj ("value" or "number")) with ((shar$3 adj "secret") or ("secret" adj "value") or "secret")) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:07 |
| L49 | 2 | l48 and ((generat$3 with ("random" adj ("value" or "number"))) with "client") | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:08 |
| L50 | 2 | l49 and (((transmitt$3 or send$3) with ("random" adj ("value" or "number"))) with "server") | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:08 |
| L51 | 2 | l50 and (((encrypt$3 or encod$3) with ("random" adj ("value" or "number"))) with "server") | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:08 |
| L52 | 0 | l51 and ((compar$3 with ("random" adj ("value" or "number"))) with (("encrypt$3 or encod$3") adj "value")) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:09 |

# EAST Search History

| | | | | | | |
|---|---|---|---|---|---|---|
| L53 | 0 | I47 and (("pre-boot" or "preboot" or ("boot" adj "server")) with authenticat$3) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:02 |
| L54 | 4 | I41 and (("pre-boot" or "preboot" or ("boot" adj "server")) with authenticat$3) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:03 |
| L55 | 0 | I54 and (("random" adj ("value" or "number")) with ((shar$3 adj "secret") or ("secret" adj "value") or "secret")) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:03 |
| L56 | 2 | I35 and (("pre-boot" or "preboot" or ("boot" adj "server")) with authenticat$3) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:07 |
| L57 | 0 | I56 and (("random" adj ("value" or "number")) with ((shar$3 adj "secret") or ("secret" adj "value") or "secret")) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:07 |
| L58 | 1606 | 380/277 | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:07 |
| L59 | 0 | I58 and (("pre-boot" or "preboot" or ("boot" adj "server")) with authenticat$3) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:09 |
| L60 | 125 | I58 and (("random" adj ("value" or "number")) with ((shar$3 adj "secret") or ("secret" adj "value") or "secret")) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:09 |
| L61 | 6 | I60 and ((generat$3 with ("random" adj ("value" or "number"))) with "client") | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:10 |
| L62 | 2 | I61 and (((transmitt$3 or send$3) with ("random" adj ("value" or "number"))) with "server") | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:10 |
| L63 | 1 | I62 and (((encrypt$3 or encod$3) with ("random" adj ("value" or "number"))) with "server") | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:10 |
| L64 | 0 | I63 and ((compar$3 with ("random" adj ("value" or "number"))) with (("encrypt$3 or encod$3") adj "value")) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:10 |

# EAST Search History

| L65 | 1504 | 380/44 | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:09 |
|---|---|---|---|---|---|---|
| L66 | 0 | l65 and (("pre-boot" or "preboot" or ("boot" adj "server")) with authenticat$3) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:11 |
| L67 | 145 | l65 and (("random" adj ("value" or "number")) with ((shar$3 adj "secret") or ("secret" adj "value") or "secret")) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:12 |
| L68 | 5 | l67 and ((generat$3 with ("random" adj ("value" or "number"))) with "client") | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:12 |
| L69 | 4 | l68 and (((transmitt$3 or send$3) with ("random" adj ("value" or "number"))) with "server") | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:12 |
| L70 | 1 | l69 and (((encrypt$3 or encod$3) with ("random" adj ("value" or "number"))) with "server") | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:12 |
| L71 | 0 | l70 and ((compar$3 with ("random" adj ("value" or "number"))) with (("encrypt$3 or encod$3") adj "value")) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:13 |
| L72 | 0 | l65 and ((compar$3 with ("random" adj ("value" or "number"))) with (("encrypt$3 or encod$3") adj "value")) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:11 |
| L73 | 0 | l58 and ((compar$3 with ("random" adj ("value" or "number"))) with (("encrypt$3 or encod$3") adj "value")) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:11 |
| L74 | 1509 | 380/46 | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:11 |
| L75 | 1 | l74 and (("pre-boot" or "preboot" or ("boot" adj "server")) with authenticat$3) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:11 |
| L76 | 0 | l75 and (("random" adj ("value" or "number")) with ((shar$3 adj "secret") or ("secret" adj "value") or "secret")) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:12 |

# EAST Search History

| | | | | | | |
|---|---|---|---|---|---|---|
| L77 | 151 | I74 and (("random" adj ("value" or "number")) with ((shar$3 adj "secret") or ("secret" adj "value") or "secret")) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:12 |
| L78 | 3 | I77 and ((generat$3 with ("random" adj ("value" or "number"))) with "client") | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:12 |
| L79 | 2 | I78 and (((transmitt$3 or send$3) with ("random" adj ("value" or "number"))) with "server") | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:12 |
| L80 | 1 | I79 and (((encrypt$3 or encod$3) with ("random" adj ("value" or "number"))) with "server") | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:13 |
| L81 | 0 | I80 and ((compar$3 with ("random" adj ("value" or "number"))) with (("encrypt$3 or encod$3") adj "value")) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:13 |
| L82 | 0 | I75 and ((compar$3 with ("random" adj ("value" or "number"))) with (("encrypt$3 or encod$3") adj "value")) | US-PGPUB; USPAT; EPO; JPO; DERWENT | OR | ON | 2007/06/29 11:13 |

Web    Images    Video    News    Maps    **more »**

**Google**™
Patent Search ◯ BETA

`random number or value and shared secret va`    [Search Patents]    Advanced Patent Search
Google Patent Search Help

Lowercase "or" was ignored. Try "OR" to search for either of two terms. [details]
The "AND" operator is unnecessary -- we include all search terms by default. [details]

## Patents

Patents **1 - 10** on **random number or value and shared secret value**. (0.10 seconds)

### Virtual dial-up protocol for network communication
US Pat. 5918019 - Filed Jul 29, 1996 - Cisco Technology, Inc.
In step 3, the remote client encrypts the **random number** R based on a remote client
password (pwd). The password 10 is a **shared secret** between remote client ...

### Network with secure communications sessions
US Pat. 5689566 - Filed Oct 24, 1995
On the other hand, in the prior art (he Rb=a 64 bit **random value** ... the **random
number** 55 generates a public key, encrypts it with a **shared secret** key Rb ...

### Payment and transactions in electronic commerce system
US Pat. 6029150 - Filed Oct 4, 1996 - Certco, LLC
The **shared secret** is a long **number** linking the merchant's quote and the cta's
... **random number** securely delivered by the CTA 102 and by a **value** randomly ...

### Method and apparatus for key-management scheme for use with internet protocols at site firewalls
US Pat. 5416842 - Filed Jun 10, 1994 - Sun Microsystems, Inc.
The key Kab is used as the key for a known livery to node J. **shared**-key ...
the lack of a public-key signa- which has been provided with the **secret value** a, ...

### Random number generating system and process based on chaos
US Pat. 5696828 - Filed Sep 22, 1995 - United Technologies Automotive, Inc.
Typical pseudo-**random number** generators are based on linear feedback shift ...
all numbers created by the **shared secret** key or public-private key set for ...

### Conditional access system
US Pat. 6157719 - Filed Jul 31, 1998 - Scientific-Atlanta, Inc.
The control word 319 is generated by **random number** generator 317. ... entitle-
15 ment agent to which the ECM 323 belongs a **shared secret** with the ...

### Distributed state random number generator and method for utilizing same
US Pat. 6628786 - Filed Sep 30, 1997 - Sun Microsystems, Inc.
A and B negotiate a **shared secret** session key K (step) using, ... When the **random
value** from the host computer's **random number** generator is added to the ...

### Network authentication method for over the air activation
US Pat. 6393270 - Filed Oct 14, 1997 - BellSouth Intellectual Property Corp.
... performing a first CAVE algorithm using the A-key **value** and a first **random
number**, the first CAVE algorithm producing a first **shared secret** data **value**; ...

### Method and apparatus for authentication in a communication system
US Pat. 5708710 - Filed Jun 23, 1995 - Motorola, Inc.

These threshold **value** then the subscriber is tagged for an A-KEY keys may include first **shared secret** data 112 (SSDA), second 65 update at 218, ...

## Pushing and pulling data in networks
US Pat. 6119167 - Filed Jul 11, 1997 - Phone.Com, Inc.
Nonce and **Random Number** Generation for the Device To implement authentication, ... during life time of a **shared secret** key), we expect that the Client Group ...

Goooooooooogle ▶

Result Page:    1 2 3 4 5 6 7 8 9 10    **Next**

| random number or value and shared secret v | Search Patents |

Google Patent Search Help | Advanced Patent Search

Google Home - About Google - About Google Patent Search

©2007 Google

Web     Images     Video     News     Maps     more »

**Google** Patent Search BETA

| encrypted value using random number or valu |     Search Patents     |

Lowercase "or" was ignored. Try "OR" to search for either of two terms. [details]
The "AND" operator is unnecessary -- we include all search terms by default. [details]

## Patents          Patents 1 - 10 on **encrypted value using random number or value and shared secret value**. (0.37 seconds)

### Method and apparatus for key-management scheme for use with internet protocols at site firewalls
US Pat. 5416842 - Filed Jun 10, 1994 - Sun Microsystems, Inc.
15 the first packet **encrypted** in key KB is the Initialization SKCS. ... packet **using**
a public-key cryptosystem is too cumber- vided with a **secret value** b, ...

### Virtual dial-up protocol for network communication
US Pat. 5918019 - Filed Jul 29, 1996 - Cisco Technology, Inc.
The password 10 is a **shared secret** between remote client 32 and home gateway 20.
... The remote client name, and the **encrypted random number** are transmitted ...

### Payment and transactions in electronic commerce system
US Pat. 6029150 - Filed Oct 4, 1996 - Certco, LLC
The **shared secret** is a long **number** linking the merchant's quote and the cta's
... The 25 transaction PIN is hashed and **encrypted using** the SHA-1 and the ...

### Conditional access system
US Pat. 6157719 - Filed Jul 31, 1998 - Scientific-Atlanta, Inc.
In the case of a true **random number**, the **encrypted** control word is ... 323 is
authenticated by **using** some or all of MSK 309 as a **shared secret** between the ...

### Network with secure communications sessions
US Pat. 5689566 - Filed Oct 24, 1995
Since the CRC signature C2 of standard. the **random number** Ra is **encrypted** and
... **random number** 55 generates a public key, encrypts it with a **shared secret** ...

### Controlled use of cryptographic keys via generating station established control values
US Pat. 4850017 - Filed May 29, 1987 - International Business Machines Corp.
... generating a **random number** in said cryptographic facility; accessing the
**encrypted secret** transport keys **shared** 65 by designated **using** stations **using** ...

### Encryption apparatus, communication system **using** the same and method therefor
US Pat. 5600720 - Filed Jul 19, 1994 - Canon Kabushiki Kaisha
1) The sender A of the communication sets all or a portion of the **secret** key KAB
**shared** by the receiver B as an initial **value** of the **random number** ...

### Secure online music distribution system
US Pat. 6385596 - Filed Feb 6, 1998 - Liquid Audio, Inc.
They negotiate a **shared secret**, a cryptographically strong **random number**, ...
that is updated by hashing the current **encrypted** data into the old hash **value**. ...

### Methods and systems for establishing a **shared secret using** an authentication token
US Pat. 6173400 - Filed Jul 31, 1998 - Sun Microsystems, Inc.

4b illustrates a method for establishing a **shared** go **secret using** a ... a password
based on the time of day **encrypted** with a **secret** code or a **random number.** ...

### Encryption device and communication apparatus **using** same
US Pat. 5666419 - Filed Nov 29, 1994 - Canon Kabushiki Kaisha
(3) The receiving party B sets all or part of the **secret** key K^g, which is **shared**
with transmitting party A, in a **random number** generator 147 as the initial ...

Goooooooooogle ▶

Result Page:      **1** 2 3 4 5 6 7 8 9 10      **Next**

encrypted value using random number or val    Search Patents

Google Patent Search Help | Advanced Patent Search

Google Home - About Google - About Google Patent Search

©2007 Google